

Shine™ Rev+P

13 BTE hearing aid



Shine Rev+ P

Sound performance features

Auto Mic		•
Sound Conductor	Noise reduction	•
	Speech enhancement	•
Separate directionality settings		•

Sound stabilization features

	AntiShock 2	•
	Feedback manager	•

Convenience features


	DuoLink	•
	Telecoil	•
	uStream compatibility	•

Fitting

	Adaptation Manager	•
	Frequency compression	•
	Tinnitus masker	•
	IntelliVent	•
	Streaming programs	•
	Manual programs	4
	NAL-NL2/NL1 and DSLv5	•
	Fitting channels	12


Shine Rev+ P is rated IP 68

Fitting guides




--- Slim tube (power dome)

ANSI 3.22 2014/IEC 60118-0: 2015 2cc coupler technical data




OSPL90

Maximum (dB SPL)	126	131
HFA - OSPL90 (dB SPL)	111	125




Full on gain (input 50 dB SPL)

Maximum (dB)	58	66
HFA - FOG (dB)	51	58




Reference test setting (RTS)

Frequency range (Hz)	<100 - 4600	<100 - 5300
Reference test gain (dB)	34	48
Current drain at RTS (mA)	1.15	1.15
Typical battery life (h)	270	270
Equivalent input noise at RTS (dB SPL)	18	19
Total harmonic distortion at 500 Hz/800 Hz/1600 Hz/3200 Hz (%)	0.2/0.2/0.5/0.5	1.7/1.2/0.7/0.7



Induction coil sensitivity (31.6 mA/m)

HFA SPLITS/STS-RSETS (dB SPL/dB)	94/0	108/0
----------------------------------	------	-------



Standard: mic at 70 dB SPL vs induction coil at 100 mA/m

--- Mic
- - - Induction Coil

Electromagnetic compatibility

EMC immunity by ANSI c63.19-2011 EMC, omni/telecoil	M4/T4	M4/T4
---	-------	-------

Legend

- Earhook
- Slimtube

Test conditions

Earhook: filtered; Battery size: 13; Source: voltage 1.3 V; Tubing: length 25 mm, inside diameter 1.93 mm
 The hearing instrument is set to Unitron Truefit test settings. LLE is applied at an approximate level of 35 dB SPL.
 Domes should never be fit on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend use of a customized earmold.
 We reserve the right to change specification data without notice as improvements are introduced.